

Notack – 507

Anti-tack Agent

Revision date : 10/04/2012

Notack– 507 is an anti-tack between surface of green compound, it can be used for most of rubber like, NR, SBR, BR, IIR, etc. Produces an excellent anti-tack effect and perfect surface appearance **without any whitish or dusty in the rubber surface.**

Have a good emulsion stability, which cause no solution homogeneity, no settling or floating problem.
Has no effect in the building tack.

Composition: A combination of metal salt of fatty acids, and different non-ionic surfactants.

Properties:

- Physical Form : Water Based Thick Liquid.
- Color : Off – White.
- Specific Gravity : ± 0.9 gr/cc.
- Odor : Mild.
- Shelf Life : 1 year

Application : It can be is applied by dipping the green compound into diluted **Notack– 507**. The dilution ratio by water is about 1 : 10 – 20 weight/weight, depend on the condition of the compound. The dilution rate some times should be adjusted with the nature of the Rubber compound.

Packaging : 100 Kgs / Drum.

The information and recommendations contained herein are based upon data believed to be correct. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Health and safety precautions detailed in this data sheet may not be adequate for all individuals and/ or situations. It is the user's obligation to evaluate and use this data in order to comply with all applicable laws and regulations. It is the user's obligation to determine the suitability of use of the product for particular application.