

# OPRA - 256

## Outside Tire Lubricant

<b>OPRA – 256</b>	is a water based, filled outside tire lubricant. When properly applied to the inside of the green tire, this product provides excellent lubrication between mold and green tire, so it will give good release.
<b>Performance :</b>	<ul style="list-style-type: none"> <li>- Viscosity prevents dripping and running during application.</li> <li>- Good surface finish.</li> <li>- This product will not become bad smell since this product is well preserved with a biocide and without containing Formaldehyde.</li> </ul>
<b>Properties:</b>	<ul style="list-style-type: none"> <li>- Appearance : Black Liquid</li> <li>- Density (kg/l, gr/cc) : <math>\pm 1</math></li> <li>- % Solids : <math>\pm 25</math></li> <li>- Viscosity (dPa.s @ 29 °C) : <math>\pm 1.5</math></li> </ul>
<b>Application:</b>	<p><b>OPRA – 256</b> can be applied by spray at ambient temperatures up to 40 °C. Coating weight will vary depending on the process. In some cases it also can be used by brushing.</p>
<b>Packaging</b>	: 100 Kgs / drum.
<b>Storage</b>	: Do not store at temperatures above 40 °C. Keep from freezing. Keep container tightly sealed to prevent evaporation and / or moisture contamination.

The information and recommendations contained herein are based upon data believed to be correct. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Health and safety precautions detailed in this data sheet may not be adequate for all individuals and/ or situations. It is the user's obligation to evaluate and use this data in order to comply with all applicable laws and regulations. It is the user's obligation to determine the suitability of use of the product for particular application.