

# EMMER – 56

## Asphalt Anti-stripping Agent

Revision Date : 11/02/2015

**EMMER – 56** is a specially formulated Antistripping Agent (Wetting Agent, Adhesion Promotor) for Asphalt, to increase adhesion and wetting properties of Asphalt in blend with Agregate.  
Usually used for **Hot Mix Asphalt** when it is processed in the Asphalt Mixing Plant (AMP).  
Have a good heat stabilisation, it doesn't loose properties in a 180 C hot asphalt for 5 days.

### Physical Properties :

Apparence in 30 °C : Brown-black Viscous Liquid  
Density gr/cc : ± 0.95 gr/cc  
Viscosity ( dpa's ) : ± 0.6 dpa's  
pH : ± 12

### Recommended dosage:

EMMER - 56 is used according to the nature Bitumen and Aggregate properties and Composition  
Under normal conditions EMMER - 56 is added between 0.2% and 0,3 % from Asphalt Content (Not from Total Asphalt and Aggregate content).

### Packaging and Storage:

EMMER - 56 packaging in 180 kg/ Drum

The information and recommendations contained herein are based upon data believed to be correct. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Health and safety precautions detailed in this data sheet may not be adequate for all individuals and/ or situations. It is the user's obligation to evaluate and use this data in order to comply with all applicable laws and regulations. It is the user's obligation to determine the suitability of use of the product for particular application.