

# NOFO – SB 03

## Antifoam and Defoamer

**Description**

NOFO – SB 03 is an antifoam agent for solvent base paint and ink.

**Composition:**

Specially formulated modified Polyether-polyester.

**Performance Features :**

- Rapid “knock down” time due to its good spreading power/high spreading coefficient
- Highly effective antifoaming and de-foaming properties
- Long lasting foam killing effect
- Relatively small dosage does not impart significant influence towards film quality.
- Good clarity.

**Typical properties:**

- Appearance : Viscous Liquid.
- Density (29° C), gr/cc : ± 1
- Non Volatile : 100 %
- Flash Point : > 150 C.
- Viscosity ( @ 29 ° C ), cps. : 725

**Recommended dosage:**

0.1 – 0.6 % based on the weight or the formulation.

**Application procedure:**

Usual practice is to add Nofo – SB 03 as it is, for antifoaming effect add it in the mill base, and for de-foaming effect add it in the let down.

**Packing:**

- 200 kg / drum
- 30 Kg / jerrycan.

The information and recommendations contained herein are based upon data believed to be correct. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Health and safety precautions detailed in this data sheet may not be adequate for all individuals and/ or situations. It is the user's obligation to evaluate and use this data in order to comply with all applicable laws and regulations. It is the user's obligation to determine the suitability of use of the product for particular application.