



SMILE-FO-PR02-R&D-13

## Silicone Grease – 08

Revision date : 22/04/2009

a a - -	<ul> <li>silicone Based Grease, which is used as lubricating gent. This product has some advantageous properties s follows :</li> <li>High Temperatures Resistance, it does not melt at until 200°C.</li> <li>Because it is Silicone Based, this product is not causing swelling for all kind of rubber.</li> <li>Gives good lubricity between rubber parts.</li> </ul>
Properties : – Appereace – Density (gr/cc) – Viscosity (Centistoke	: White Translucent Non Flowing Grease. : <u>+</u> 1 s, Cst) : <u>+</u> 60,000.
<b>Application :</b> Apply Silicone Grease-08 to the part which would be lubricated by manual or injection.	
<b>Storage</b> : Keep container tightly sealed to prevent dirt contamination.	
Packaging: 15 Kgs / pail.	

The information and recommendations contained herein are based upon data believed to be correct. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Health and safety precautions detailed in this data sheet may not be adequate for all individuals and/ or situations. It is the user's obligation to evaluate and use this data in order to comply with all applicable laws and regulations. It is the user's obligation to determine the suitability of use of the product for particular application.