

# IPRA- 634

## Filled Inside Tire Lubricant

<p><b>IPRA - 634</b> is a water based , filled inside tire lubricant. When properly applied to the inside of the green tire, this product provides excellent lubrication between the bladder and the green tire.</p>
<p><b>Performance :</b></p> <ul style="list-style-type: none"><li>- Viscosities prevents dripping and running during application, when properly applied.</li><li>- Give good coverage for the cord.</li></ul>
<p><b>Composition:</b></p> <p><b>IPRA-634</b> is specially formulated tire lubricant consisting special release blends; and some fillers.</p>
<p><b>Properties:</b></p> <ul style="list-style-type: none"><li>- Appearance : Black Thick Liquid (color can be adjusted).</li><li>- Density (kg/l, gr/cc) : <math>\pm 1</math></li><li>- Solid Content : <math>\pm 35 \%</math></li><li>- Viscosity (@ 30°C) : <math>\pm 2</math> dpa's</li></ul>
<p><b>Application:</b></p> <p><b>IPRA 634</b> can be applied by spray at ambient temperatures up to 40°C. Coating weight will vary depending on the process. In some cases it also can be used by brushing.</p>
<p><b>Packaging</b> : 100 Kg / drum.</p>

The information and recommendations contained herein are based upon data believed to be correct. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Health and safety precautions detailed in this data sheet may not be adequate for all individuals and/ or situations. It is the user's obligation to evaluate and use this data in order to comply with all applicable laws and regulations. It is the user's obligation to determine the suitability of use of the product for particular application.